

● SPECIFICATION

| | | |
|----------------------------------|--------|--|
| Cooling Capacity | BTU/h | 84,000 |
| Power Supply | Volts | 3ph/480V/60Hz |
| Size(WxDxH) | inch. | 29.1x55.1x458.7 |
| Weight | lbs | 550 |
| Current Consumption(AMPS) | A | 15.4 |
| Circuit Breaker Size(AMPS) | A | 20 |
| Rated Power Consumption(Cooling) | kW | 12.8 |
| Compressor Input | kW | |
| Air Flow(CMP,High/Low)Evaporator | CFM | 2,200/1,800 |
| Air Flow(CMP,High/Low)Condenser | CFM | 3,200 |
| Motor Input | kW | 1.7 |
| Air Filter | | Aluminum Filter |
| Nema Plug | | |
| Safety Device | | <ul style="list-style-type: none"> • High/Low Pressure Switch • Fan Motor Protection • 3min, Delay Timer • Automatic Full Tank Shut-Off • Thermostat Protector for Compressor |
| Static Pressure | psi | 710 |
| Power Cord | type | TERMINAL TYPE |
| Power Cord Length | ft | 32.8 |
| Outlet Air Velocity | ft/sec | 46 |
| Outlet Temp. Difference | °F | 50~59 |
| Refrigerant | lbs | R-410A(8.82) |
| Operating Conditions | °F | 72°F DB 60%RH~113°F DB 40%RH |
| Maximum Duct Length | ft | 65.6 |

The specification and design of the product above are subject to change for the performance improvement without notice.

● Ideal applications for Airrex Portable Air Conditioner



Industrial Sites > Temperature work sites, Car manufacturing, plants, Ship building yards and steel mills.

Repair Shops > Car repair shops, Aircraft workshops, Farm machinery workshops, Gas stations and parking facilities

Heat Generating Equipment > Server rooms and machine rooms

Leisure / Outdoor Event Venues

Farm & Livestock Ranges