

CAMPO EQUIPMENT

6 Carson Court, Brampton, ON, L6T 4P8 1-866-323-0042 www. campoequipment.com



BLAZE 400D TURBO

- ✓ Input BTU/h: 280,000 to 396,000
- ✓ Indirect Oil Fired
- ✓ Beckett Burner (4 Firing Rates)
- ✓ 220 °F + Heat Rise
- ✓ Ductability: 150 ft. (Turbo)
- ✓ Fuel Tank: 42 US Gallons (Optional 70 and 100 US Gallon tank available)
- ✓ Whisper Quiet Operation
- ✓ Air Volume (CFM): 5,500 (Turbo) Up to 3" of Static pressure
- ✓ Recirculating Capabilities
- ✓ Thermostat Operation
- ✓ Genysis Primary Controller
- ✓ Redundant Fail Safe Control System
- ✓ Digital Panel Mounted Voltmeter
- ✓ Oil Pressure Gauge, Spin-off Filter
- ✓ Lifting Bar & Forklift Pockets
- ✓ Weight: 550 lbs.
- ✓ Dimensions: 76.7" x 31" x 57.6"
- ✓ Full Load Amps: 8.5A (Turbo)
- ✓ Power Supply: 120 Volt, 15 A
- ✓ Air Outlets: Two 12" or 1 x 16"
- ✓ Air Inlets: Two 12" or 1 x 16"
- ✓ Stainless Steel Heat Exchanger
- ✓ CSA/UL Approved



Optional 120% spill containment on 42 and 70 Gallon tanks available for 400/600 Series

BLAZE 400G TURBO & BLAZE 600G TURBO I & II

- ✓ Input BTU/h: 399,000 (400G), 575,000 (600GT & 600GTII)
- ✓ Indirect NG/LP
- ✓ Beckett Burner
- ✓ 220 °F + Heat Rise
- ✓ Ductability: 150 ft
- ✓ Whisper Quiet Operation
- ✓ Air Volume (CFM): 5,500 (400G/600G), 6,500 (600GTII)
- ✓ Up to 3" of Static pressure (400G), 4" of Static pressure (600GT & 600GTII)
- ✓ Recirculating Capabilities
- ✓ Thermostat Operation
- ✓ Digital Panel Mounted Voltmeter
- ✓ NG/LP Easy Switchover valve
- ✓ Redundant Fail Safe Control System
- ✓ Lifting Bar
- ✓ Forklift Pockets
- ✓ Weight: 550 lbs (400G) 600lbs (600G/600GTII)
- ✓ Dimensions: 76.7" x 31" x 57.6"
- ✓ Full Load Amps: 8.5 A (400G)/11.5A (600G) 18A (600G TII)
- ✓ Power Supply: 120 Volt, 15 A (400G/600G) 120 Volt, 20 A (600GTII)
- ✓ Air outlets: Two 12" or 1 x 16"
- ✓ Air Inlets: Two 12" or 1 x 16"
- ✓ Stainless Steel Heat Exchanger
- ✓ CSA/UL Approved



BLAZE 600D TURBO I & II

- ✓ Input BTU/h: 588,000
- ✓ Indirect Oil Fired
- ✓ Beckett Burner
- ✓ 240 °F + Heat Rise
- ✓ Ductability: 150 ft. (Turbo)
- ✓ Fuel Tank: 42 US Gallons (Optional 70 and 100 US Gallon tank available)
- ✓ Whisper Quiet Operation
- ✓ Air Volume: 5,500 CFM or 6,500 CFM
- ✓ Up to 4" of Static pressure
- ✓ Recirculating Capabilities
- ✓ Thermostat Operation
- ✓ Genysis Primary Controller
- ✓ Digital Panel Mounted Voltmeter
- ✓ Redundant Fail Safe Control System
- ✓ Oil pressure gauge, Spin-off Filter
- ✓ Lifting Bar
- ✓ Forklift Pockets
- ✓ Weight: 600 lbs.
- ✓ Dimensions: 76.7" X 31" X 57.6"
- ✓ Full Load Amps: 11.5/18
- ✓ Power Supply: 120 Volt, 15 A/20 A
- ✓ Air Outlets: Two 12" or 1 X 16"
- ✓ Air Inlets: Two 12" or 1 X 16"
- ✓ Stainless Steel Heat Exchanger
- ✓ CSA/UL Approved
- ✓ OPTIONAL 70 and 100 US Gallon Tanks for 400/600 Series
- ✓ Optional 120% spill containment on 42 and 70 Gallon tanks



BLAZE 700D/G

- ✓ Input BTU/h: 700,000
- ✓ Oil/Gas Fired
- ✓ Beckett/Riello Burner
- ✓ 3 Fan Speeds up to 10,000 CFM
- ✓ High Static Fan: up to 4" Static Pressure
- ✓ Ducting: up to 200 ft., 1 x 20" duct panels on supply side
- ✓ Full Load Amps: 1PH 16 Amps, 3PH 8.5 AMPS
- ✓ Voltage: 1PH or 3PH/208-240V
- ✓ Weight: 1,200 lbs.
- ✓ Dimensions: 92" x 33.25" x 45"



BLAZE 1000D/G

- ✓ Input BTU/h: 1,000,000
- ✓ Oil/Gas Fired
- ✓ Beckett Burner
- ✓ 3 Fan Speeds up to 13,500 CFM
- ✓ High Static Fan: up to 6.5" Static Pressure
- ✓ Ducting: up to 400 ft., 1 x 24" duct panels on supply and return side
- ✓ Full Load Amps: 1PH 42 Amps, 3PH 25 AMPS
- ✓ Voltage: 1PH or 3PH/208-240V
- ✓ Weight: 2,000 lbs.
- ✓ Dimensions: 111" x 33.25" x 50"



BLAZE 2000D/G

- ✓ Input BTU/h: 2,000,000
- ✓ Oil/Gas Fired, Beckett Burner (High Fire /Low Fire Burner)
- ✓ 3 Fan Speeds up to 16,000 CFM
- ✓ High Static Fan: up to 6.5" Static Pressure
- ✓ Ducting: up to 200 ft. 1 x 24" duct panel on supply and return side
- ✓ Full Load Amps: 1PH 55 Amps, 3PH 32 Amps
- ✓ Voltage: 1PH or 3PH/208-240V
- ✓ Weight: 2950 lbs.
- ✓ Dimensions: 144" x 33.25" x 67"



700/1000/2000 D/G Common Features:

- ✓ Indirect Fired
- ✓ Recirculating Capabilities
- ✓ Tempered Air Mode for LEED Construction allows for lower discharge temperature when remote thermostat is satisfied in order to deliver continuous heat to the jobsite (Standard on Blaze 1000 and 2000, optional on Blaze 700)
- ✓ NG/LP easy switch over valves
- ✓ Gas Pressure Gauges on Manifold and inlet side of train
- ✓ Panel Mount Voltmeter
- ✓ Genysis Display Module (Oil Units) provides critical diagnostic info.
- ✓ Hour meter
- ✓ VFD Eliminates Large in-rush Current for Motor Starts
- ✓ Stackable for off-Season Storage
- ✓ Optional "Plug and Play" burner kit can easily convert unit from diesel to NG or LP
- ✓ Available in 3 fuel options upon ordering: Natural Gas/Propane/Diesel
- ✓ High Efficiency heaters: 88%
- ✓ Able to fit through a 36" door opening
- ✓ Mobile and easy to position around the job site with integrated Fork Lift Pockets and Lifting Eyes
- ✓ Stainless Steel Heat Exchangers
- ✓ Units Feature Extra Large Burner Compartment for ideal service access or simple burner conversion
- ✓ CSA/UL Approved